

## Rubber Conveyor Skirting

### Black Natural Skirting Rubber

(65 shore 'A' & Tensile Strength: 3 MPA), the traditional product of choice and is still widely used today in the quarry, mining and materials handling industries. AEG keep a wide range in stock for your immediate access.

THICKNESS	WIDTH	LENGTH	HARDNESS
10mm	100mm	30	65 Shore
10mm	150mm	30	65 Shore
10mm	200mm	30	65 Shore
10mm	250mm	30	65 Shore
10mm	300mm	30	65 Shore
12mm	100mm	30	65 Shore
12mm	150mm	30	65 Shore
12mm	200mm	30	65 Shore
12mm	250mm	30	65 Shore
12mm	300mm	30	65 Shore



### Orange Skirting Rubber

(40 shore 'A' & Tensile Strength: 16 MPA) has better abrasion resistant properties with up to 3-5 times the wear life of black natural skirting rubber.

Sold in 15m rolls



THICKNESS	WIDTH	LENGTH	HARDNESS
10mm	100mm	15	40 Shore
10mm	150mm	15	40 Shore
10mm	150mm	10	40 Shore
10mm	200mm	15	40 Shore
12mm	100mm	15	40 Shore
12mm	150mm	15	40 Shore
12mm	200mm	15	40 Shore
12mm	200mm	10	40 Shore
12mm	250mm	15	40 Shore
12mm	300mm	15	40 Shore

#### Brisbane

Unit 2/75 Metroplex Place  
Wacol QLD 4076  
(07) 3713 7744

**aeg-group.au**

#### Melbourne

33 Castro Way  
Derrimut VIC 3026  
(03) 9363 1577